







PANEL CUT-OUT



HARDWARE:



Tolerances: 0.00: ±0.25mm 0.0: ±0.40mm			Date	Name	<b>DPWL 1 CG-xy</b>
			02/08	dr	
LED colour table	06/10	dr	<b>knitter-switch</b>		<b>30 13 72</b>
Actuator color black	06/08	dr			
Operating temperature	04/08	dr			
Water proofing	04/08	dr			
Modifications	Date	Name			
					Page 1/2

**Specifications:**

Contact rating: max.: 400mA, 32V AC; 100mA, 50V DC; 125mA, 125V AC  
 Contact resistance: 50mOhm max.  
 Insulation resistance: 1GOhm min at 500V DC  
 Dielectric strength: 1 000V AC RMS  
 Operating temperature: -30°C to +85°C  
 Electrical life: 500 000 cycles at full load  
 Operating force: 2N - 5N  
 Contact bounce: 10 ms  
 Torque: 0.5Nm max. applied to nut  
 Soldering conditions: 300°C max., 3sec.  
 Total travel: 1.5mm  
 Panel thickness: 1.5mm min., 4.0mm max.  
 Water proofing: IP 67  
 Material: Case: DAP UL94V-0  
 Cap / bushing: polyamide 6/6  
 Terminal / contacts: gold over silver plated

Lens appearance	Colour	Electro-optical data (at 20mA)				Peak wavelength	Viewing angle
		Vf (V)		Iv (mcd)			
		Typ.	max.	Typ.	max.		
Water clear	white (at 5mA)	3.2	3.6	250.0	94.0	x=0.28 y=0.29	35°
	super red	1.7	2.6	60.0	28.0	660.0	
	super yellow	2.1	2.6	200.0	94.0	590.0	
	super green	2.0	2.6	100.0	42.0	570.0	
	super blue	3.2	3.6	150.0	63.0	470.0	
	super yellow	2.1	2.6	200.0	94.0	590.0	
	super green	2.0	2.6	80.0	42.0	570.0	
	super yellow	2.1	2.6	200.0	94.0	590.0	
	super blue	3.2	3.6	200.0	94.0	460.0	
	super yellow	2.1	2.6	100.0	63.0	590.0	
	super red	2.0	2.6	90.0	42.0	630.0	
	super red	2.0	2.6	90.0	42.0	630.0	
	super red	2.0	2.6	90.0	42.0	630.0	
	super blue	3.2	3.6	200.0	94.0	460.0	
super green	2.0	2.6	100.0	42.0	570.0		
super blue	3.2	3.6	200.0	94.0	460.0		

X=CAP COLOR	
W	white
K	black
R	red
O	orange
Y	yellow
G	green
B	blue

Y=LED COLOR	
W	white
R	red
Y	yellow
G	green
B	blue
YG	yellow / green
YB	yellow / blue
YR	yellow / red
RG	red / green
RB	red / blue
GB	green / blue

**SWITCH FUNCTION**

Model No.	POS. 1	POS. 2
DPWL 1 CG	OFF	MOM
Term. Conn.	OPEN	SHORT



Tolerances: 0.00: ±0.25mm 0.0: ±0.40mm		Date	Name	DPWL 1 CG-xy
		02/08	dr	
				<b>30 13 72</b>
<b>knitter-switch</b>				
Modifications				Page
				2/2