



Specifications:

Contact rating: switching: 15mA, 24V DC
 non-switching: 100mA, 50V DC
Contact resistance: 80mOhm max.
Insulation resistance: 100MOhm min.
Mechanical life: 10 000 cycles
Operating force: 700gf max.
Operating temperature: -40°C to +85°C
Storage temperature: -40°C to +85°C
Soldering conditions: pre-heat: max. 120°C, max. 70sec.
 wave soldering: max. 260°C, max. 10sec.
Color of actuator: grey
IP rating: IP67

		Hexadecimal				
		C	1	2	4	8
16 P o s i t i o n s	0	●				
	1	●	●			
	2	●		●		
	3	●	●	●		
	4	●			●	
	5	●	●			●
	6	●		●		
	7	●	●	●	●	
	8	●				●
	9	●	●			●
	A	●		●		●
	B	●	●	●	●	
	C	●			●	
	D	●	●		●	●
	E	●		●	●	●
	F	●	●	●	●	●



Tolerances: ≤ 10mm:	Date	Name
≥ 10mm:	08/07	dr
Soldering conditions	01/11	dr
IP rating	06/09	dr
Operating temperature	11/08	dr
Temperatures	01/08	dr
Modifications	Date	Name

DRR 60016-1

knitter-switch

30 11 93

Page

1/1