


Specifications:

Contact rating: 3A, 250V AC
 Contact resistance: 50mOhm max.
 Insulation resistance: 1 000MOhm min. at 500V DC
 Dielectric strength: 2 000V RMS (50/60Hz)
 Operating temperature: -40°C to +85°C
 Electrical life: 50 000 cycles
 Operating force: 4N max.
 Torque: 5-14Nm max. applied to nut
 Switching function: on - mom
 IP class: IP67 protection
 IK class: 09
 Illumination: by LED, integrated shunt, use 6V AC/DC operating voltage

Material:
 Bushing / button: nickel plated brass with varnished polished
 Contact: silver alloy
 Nut: nickel plated brass
 Base: PBT

CONTACT CONFIGURATION



LED POLARITY

+ red
 - green

x	LED color
R	red
G	green
Y	yellow
O	orange
B	blue
W	white
RG	red / green Dual-LED



Tolerances: 0.00 to 30.00: ±0.20mm		Date	Name
30.01 to 80.00: ±0.25mm		03/09	dr
Operating temperature	05/11	dr	
IK class	06/10	dr	
Operating temperature	04/10	dr	
LED	03/10	dr	
Modifications	Date	Name	

MAV02LB3M3FDx6V

knitter-switch

30 17 46

Page

1/1