


P.C. MOUNTING



SWITCH FUNCTION

| Model No.   | POS. 1 | POS. 2 | POS. 3 |
|-------------|--------|--------|--------|
|             |        |        |        |
| MFP 126 DB  | ON     | NONE   | ON     |
| Term. Conn. | 2-1    | OPEN   | 2-3    |

Specifications:

Contact rating: 0.4VA max.; 20V max. (AC or DC)  
 Contact resistance: 10mOhm max. at 2-4V DC  
 Insulation resistance: 1 000MOhm min.  
 Dielectric strength: 1 000V RMS  
 Operating temperature: -30°C to +85°C  
 Mechanical life: 30 000 make-and-break cycles  
 Soldering conditions: 260°C, 10sec. max.  
 Material: Case: PMC, black  
 Actuator: nylon, black  
 Housing: stainless steel  
 Contact: gold plated



|   |      |       |                       |                          |
|---|------|-------|-----------------------|--------------------------|
| Tolerances: 0.00: ±0.25mm<br>0.0: ±0.40mm |      | Date  | Name                  | <h1>MFP 126 DB-RA-S</h1> |
|   |      | 02/08 | dr                    |                          |
|   |      |       |                       |                          |
|   |      |       |                       |                          |
|   |      |       | <b>knitter-switch</b> | <h2>30 13 81</h2>        |
|   |      |       |                       |                          |
| Modifications                             | Date | Name  |                       |                          |