


P.C. MOUNTING



CONTACT ARRANGEMENT

| code for x | function | actuator in position 1 | actuator opposite to pos. 1 |
|------------|----------|------------------------|-----------------------------|
| D | On-On | 1-2 | 2-3 |
| H | On-Mom | | |

| code for x | function | actuator in position 1 | actuator in center | actuator opposite to pos. 1 |
|------------|-----------|------------------------|--------------------|-----------------------------|
| E | On-Off-On | 1-2 | open | 2-3 |

SWITCH RATING

| code for y | contacts and terminals | rating AC with real load | rating DC with real load |
|------------|-------------------------------------|--------------------------|--------------------------|
| empty | silver-plated over nickel | 2A/250V, 5A/125V | 5A/28V |
| B | gold-plated over nickel | 0.4VA/20V | 0.4VA/20V |
| G | gold-plated over silver over nickel | 2A/250V, 5A/125V | 5A/28V |

Specifications:

- Contact rating: 0.4VA max., 20V max. (AC or DC)
- Contact resistance: 10mOhm max. at 2-4V DC
- Insulation resistance: 1 000MOhm min.
- Dielectric strength: 1 000V RMS
- Operating temperature: -30°C to +85°C
- Mechanical life: 30 000 make-and-break cycles
- Material: Case: diallyl phthalate (DAP) (UL94V-0)
Actuator: nylon, black
Housing: stainless steel
Contact: gold plated



| | | |
|---|-------|------|
| Tolerances: 0.00: ±0.25mm 0.0: ±0.40mm | Date | Name |
| | 02/10 | dr |
| | | |
| | | |
| | | |
| Switch rating | 05/10 | dr |
| Switching function | 05/10 | dr |
| Modifications | Date | Name |

MFP 126 x y S2-VS2

30 20 13

Page

1/1

knitter-switch