



**PANEL MOUNTING**



**P.C. MOUNTING**



**Specifications:**

- Contact rating: 0.4VA max.; 20V max. (AC or DC)
- Contact resistance: 20mOhm max. at 2-4V DC
- Insulation resistance: 1 000MOhm min.
- Dielectric strength: 1 500V RMS
- Operating temperature: -30°C to +75°C
- Mechanical life: 50 000 make-and-break cycles
- Cap installation force: 10 lbs, max. permissible
- Switching function: on - mom
- Material: Case / bushing: glass filled nylon 6/6, flame retardant, heat stabilized (UL94V-0)  
 Plunger: glass filled nylon (UL94V-0)  
 Switch support: brass or steel, tin plated  
 Switch support retainer: stainless steel  
 N.O. / N.C. contacts: brass, gold plated  
 Common contacts / all terminals: copper alloy, gold plated  
 Terminal seal: epoxy



|   |       |      |
|---|-------|------|
| Tolerances: 0.00: ±0.25mm<br>0.0: ±0.40mm | Date  | Name |
|   | 08/05 | dr   |
|   |       |      |
|   |       |      |
|   |       |      |
|   |       |      |
| RoHS compliant                            | 03/11 | dr   |
| Modifications                             | Date  | Name |

**MPME 1 FB B20**

**30 06 69**

**knitter-switch**

Page

1/1