




SWITCH FUNCTION

| Model No. | POS. 1 | POS. 2 |
|-------------|---|---|
| |  |  |
| TSP 2 C | OFF | MOM |
| Term. Conn. | OPEN | 1-3, 4-6 |

P.C. MOUNTING



Specifications:

- Contact rating: 0.4VA max.; 20V max. (AC or DC)
- Contact resistance: 20mOhm max. at 2-4V DC
- Insulation resistance: 1 000MOhm min.
- Dielectric strength: 1 000V RMS
- Operating temperature: -30°C to +85°C
- Mechanical life: 50 000 make-and-break cycles
- Soldering conditions: auto-soldering: 260 +/-5°C, 5 +/-1sec.
- Material: Case: glass filled nylon 66, flame retardant, heat stabilized (UL94V-0)
Plunger: thermoplastic polyester (UL94V-0)
Switch support: brass, tin plated
Contact: gold plated copper alloy



| | | |
|---|-------|------|
| Tolerances: 0.00: ±0.25mm 0.0: ±0.40mm | Date | Name |
| | 01/08 | dr |
| | | |
| | | |
| | | |
| Switch support | 10/08 | dr |
| Soldering conditions | 10/08 | dr |
| Modifications | Date | Name |

TSP 2 C-RA

30 13 48

Page

1/1

knitter-switch