



Toggle is shown in position 1



P.C. MOUNTING



Specifications:

- Contact rating: 0.4VA max., 20V max. (AC or DC)
- Contact resistance: 20mOhm max. at 2-4V DC
- Insulation resistance: 1 000MOhm min.
- Dielectric strength: 1 000V RMS
- Operating temperature: -30°C to +85°C
- Mechanical life: 50 000 make-and-break cycles
- ESD resistance: 6kV
- Material: Case / bushing: glass filled nylon 6/6, retardant, heat stabilized (UL94V-0)
Actuator: glass filled nylon 6/6
Terminals / contact: gold plated copper

CONTACT ARRANGEMENT

code for x	function	toggle in position 1	toggle opposite to pos. 1
N	On-On	2-3, 5-6	1-2, 4-5
R	On-Mom		

code for x	function	toggle in position 1	toggle in center	toggle opposite to pos. 1
P	On-Off-On	2-3, 5-6	open	1-2, 4-5
S	Mom-Off-Mom			
T	On-Off-Mom			
PA	On-On-On	2-3, 5-6	2-3, 4-5	1-2, 4-5
SA	Mom-On-Mom			
TA	On-On-Mom			



Tolerances: 0.00: ±0.25mm 0.0: ±0.40mm	Date	Name
	05/09	dr

TST 2 x ESD

Modifications	Date	Name	knitter-switch	30 18 20	Page
					1/1